IC-F29SR Licence-free Radio Features



1500_{mw} Ultra Powerful Audio

This simple to use radio is ideal for high turnover environments and shift work where the radio is constantly passed from person to person.

Icom custom high power handling capacity speaker for 1500 mW powerful audio. Hear calls destined for you in all sorts of environments.



16-position rotary channel knob can be programmed with operating channels and group code. The radio announces the channel number, when you rotate it.



The Smart-Ring function checks whether the receiver is in communication range with a ringer sound.

Private Conversation

Group Call

The user programmable

CTCSS and DTCS codes can

be used for group call. You will

only send a call to specified

group members using the

same tone and same channel.

Call-Ring

The Call-Ring function can be

used to call receivers with a

ringer tone. Ten different ring

patterns can be selected.

The built-in inversion voice scrambler provides private conversation. Up to 16 codes are selectable.



The supplied Li-Ion battery pack, BP-279, provides up to 21 hours of operating time. The supplied rapid charger BC-213 charges the BP-279 in 2.5 hours.

Other Features

- Low battery alert
- Monitor function
- Surveillance function
- Microphone gain level adjustment
- Three programmable buttons
- Time-out-timer function Siren alarm function
- Key lock function
 - Power on scan function PC programmable

Specifications

- Usable channels: 8 channels
- Output power: 500 mW (ERP)
- Audio output power: Internal speaker 1500 mW typ. (with 8 Ω load) External speaker 400 mW typ. (with 8 Ω load) (at 5% distortion)
- Dimensions : 52.2 (W) × 186.1 (H) × 24.5 (D) mm (with BP-279)
- 240 g (with BP-279) Weight:
- Communication range*: Approx. 8 km (Wide open space)
- Operating temperature: -25°C to +55°C
- IP rating: IP67 (Dust-tight and waterproof protection)
- Military standrad: MIL-STD-810-G
- * Communication range may differ depending on operating environment or weather conditions, etc. All stated specifications are subject to change without notice or obligation.

Supplied Accessories





Battery packs

BP-278

BP-279

BP-279

Type

Li-ion 7.2 V

Li-ion 7.2 V

Li-ion 7.2 V



Rapid charger BC-123SE/SUK* BC-213

Battery pack MB-133 (* May differ depending on version)

Batteries & Charger Options



AC adapter





BC-214 OPC-656 Rapidly charges up to six transceivers For use with and/or battery packs at the same time. BC-214.

www.icom.co.ip/world

CP-23L For use with BC-213.

lcom, lcom Inc. and the lcom logo are registered trademarks of lcom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand, and/or other countries.

Icom (Europe) GmbH http://www.icomeurope.com

Icom (UK) Ltd. http://www.icomuk.co.uk

Icom Inc.

Icom Spain S.L. http://www.icomspain.com

Icom France s.a.s. http://www.icom-france.com



Compact & Slim IP67 Waterproof

Tough & Rugged

ĭсом

100

. - IT

PMR446 TRANSCEIVER

IC-F29SR

DIMIC



ACTUAL

SIZE

Extensive Optional Accessories

Our range of optional Icom microphones and headsets increases the flexibility of your team in the workplace.





pact size speaker-

microphone.



Headsets

HS-94LWP Earhook headset with boom microphone and waterproof connector. Provides handsfree operaation.

> HS-95LWP Behind-the-head type with boom microphone and waterproof connector. Provides hands-free operation.

HS-97 + VS-4LA or OPC-2004LA Throat microphone picks up your speech vibration even in a noisy environment.

VS-4LA PTT SWITCH CABLE OPC-2004LA PLUG ADAPTER CABLE Either VS-4LA or OPC-2004LA is required when using HS-97 headset.